



**HAL**  
open science

## Corrosion in MEG reclaiming systems : impact of operating conditions

Jean Kittel, Gaurav R Joshi, Guillaume Parer, François Quinio

► **To cite this version:**

Jean Kittel, Gaurav R Joshi, Guillaume Parer, François Quinio. Corrosion in MEG reclaiming systems : impact of operating conditions. Eurocorr 2021, Sep 2021, Budapest, Hungary. hal-03545304

**HAL Id: hal-03545304**

**<https://ifp.hal.science/hal-03545304>**

Submitted on 27 Jan 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Corrosion in MEG reclaiming systems : impact of operating conditions

Jean KITTEL<sup>1</sup>, Gaurav, R. JOSHI<sup>1</sup>, Guillaume PARER<sup>2</sup>, François QUINIO<sup>2</sup>

<sup>1</sup> IFP Energies nouvelles, France

<sup>2</sup> Axens, France

Mono ethylene glycol (MEG) is often injected in gas transport lines to prevent the formation of hydrates. In addition to natural gas, transported fluids may also contain condensates, water – either condensed or coming from the formation -, and salts - either dissolved or already precipitated.

Axens' robust and versatile reclamation technology, AdvaMEG®, uses a vacuum distillation and purification system protected by several patents, which allows the removal of water from the rich MEG (aqueous MEG stream recovered after gas and condensate separation step) but also all types of salts originating from the formation water and from the flow assurance loop.

After entering in a low pressure separator resulting in the removal of hydrocarbons and acid gases, the rich-MEG stream enters the Reclaimer Flash Separator, which is the core of the reclamation unit. This equipment is operated at low pressure (approximately 200-600 mbar) and a relatively high temperature (110 – 150 °C). There, most of the water and MEG are evaporated while salts tend to accumulate and precipitate at the bottom of the reclaimer flash separator. Although most of dissolved acid gases are flashed from the rich MEG stream, residual acidity may persist in the reclaiming loop. In addition, since several steps are operated under vacuum, air ingress could occur. Therefore, MEG streams in the reclaiming loop could contain corrosive compounds. To overcome corrosion problems, chemicals such as caustic soda or sodium carbonate are injected in the reclaiming loop to increase the pH and limit the risks of corrosion. pH control also enhances the precipitation of certain dissolved salts, thereby improving the efficiency of the purification process. Several technology providers request to use corrosion resistant alloys such as duplex stainless steels. However, it is the goal of this paper to evaluate the compatibility of carbon steel in those conditions.

In this communication, we will describe an integrated MEG-reclaiming process using carbon steels metallurgy for most of the lines and vessels that handle slurry solutions (MEG solution saturated with salts and containing suspended solids). Results of corrosion tests in MEG solutions at various pH levels from acid (close to pH 4) to alkaline (pH above 10) values at a temperature of 120 °C will be presented to demonstrate that carbon steel could be used in reclaiming application operating under certain conditions. A comparison between NaOH and Na<sub>2</sub>CO<sub>3</sub> for pH control will be presented, as well as the impact of oxygen contaminations on corrosion rates.